Red Grandis





Exclusive species to Timbmet

This South American species, which is 100% FSC certified, is a high-grade clear timber with consistency in colour, appearance, grain and workability. Often used in furniture, cabinets, mouldings and within the window and door frame industry. Red Grandis can easily be finished to resemble other species such as Oak and Meranti, alternatively it can be left untreated to weather to an attractive silver grey colour.

Generic specific name: *Eucalyptus grandis* Geographical area: South America Durability: Class 2 durable to Class 3 moderately durable Appearance: light red to pinkish brown,

mild grain with even texture

SAWN

FAS grade, to NHLA grading rules

Length: 2.4m to 4.8m lengths

Width: strips available in 5", 6", 7", random widths from 6.5" and wider

Thickness: available in 1" 25.4mm, 1¹/₄" 32mm, 1¹/₂" 38mm, 2" 50.8mm – all surfaced 2 sides.

MOULDINGS

Mouldings – Internal mouldings such as skirting, architrave and thresholds manufactured to order

Decking – External decking boards manufactured to order

Cladding - Exterior profiles manufactured to order

Sawn: square-edged, strips and FAS Drying: kiln-dried

Spec: 1.8m and longer, 75mm and wider **Weight:** 595 kg/m³ average at 15% moisture **Uses:** furniture, mouldings, exterior and interior joinery

TEC

Window sections – ideal for sash, casement and frame manufacture. 3ply and 4ply scantlings 63, 72 or 96mm thickness x 75 or 95mm wide. All lengths are 2.0m and longer.

Door sections – ideal for stile, muntin, rail and head manufacture. 3ply and 4ply scantlings at 48, 63 or 72mm thickness x 95 or 120mm wide. Mid and bottom rails available in 200mm widths. All lengths are 2.0m and longer.

Frame sections. 4ply construction at a thickness of 96mm x 75mm face. Lengths supplied are all 2.0m and longer.

Standard TEC properties and benefits apply, this includes the supply of all stock free of finger joints to the exposed faces.

TEC benefits from dimensional stability, reduced wastage and costs, a flawless finish without knots, splits and no finger joints to the exposed faces.

• West Region: **t** 01865 860350

• East Region: **t** 01865 860351

• Scotland: **t** 0141 440 0060

• Ireland: **t** +44 (0) 1865 860620

e: marketing@timbmet.com www.timbmet.com

Everything wood should be