

Off the shelf TEC



WINDOW TEC™

Species

Idigbo, Iroko, Meranti, FSC European Oak, Sapele, Certified Redwood and **NEW FSC Red Grandis**.

Sash or Casement

- All species 63 x 75mm and 72 x 75mm
- 63 x 63mm, 63 x 95mm, 72 x 63mm and 72 x 86mm in Certified Redwood only
- Hardwood in lengths of 1.2m and longer
- Softwood in lengths of 6.0m only

Outer Frame, Jambs and Head Section

- 96 x 63mm and 96 x 75mm
- Hardwood in lengths of 1.2m and longer
- Softwood in lengths of 6.0m only

Performance

All sections achieve FD30 Fire Rating.



STAIR TEC™

Species

Oak and edge-glued pine available from stock. Other species available to order.

Stair String

- Oak – 32 x 275mm x 4.8m
- Pine – 27 x 270mm x 5.1m & 32 x 275mm x 5.1m

Stair Tread

- Oak – 32 x 275mm in lengths of 1.0m and 1.2m
- Pine – 27 x 269mm in lengths of 5.1m

NEW Stair Riser

- 18 x 225mm in lengths of 1.0m and 1.2m
- Available in Oak only

Newel Post

- Oak – 90 x 90mm and 115 x 115mm in lengths of 1.7m to 3.0m
- Pine – 96 x 96mm in 6.0m lengths



DOOR TEC™

Species

Idigbo, Iroko, Meranti, FSC European Oak, Sapele, Certified Redwood and **NEW FSC Red Grandis**.

Stile/Muntin/Top Rail

- 48 x 95mm, 48 x 120mm, 63 x 120mm, 72 x 95mm, 72 x 120mm
- All lengths of 2.0m and longer
- 63 x 125mm available in Certified Redwood and Red Grandis only

Mid/Bottom Rail

- Hardwood – 48 x 200mm, 63 x 200mm, 72 x 200mm in lengths of 1.0m or 1.2m
- Softwood – 48 x 220mm, 63 x 220mm, in lengths of 0.8m to 1.2m

Outer Frame, Jambs and Head Section

- All species 96 x 63mm and 96 x 75mm
- Hardwood in lengths of 2.0m and longer
- Softwood in lengths of 6.0m only

Performance

All sections achieve FD30 Fire Rating.



Insulated Door Panels

For the highest levels in thermal and acoustic insulation, the TEC range of engineered door panels can't be beaten. Eliminating the need for return site visits, they are ideal if you have energy saving requirements.



28mm insulated door panel

- 28mm high density cork-filled door panels are ideal for tongue-and-grooved and flat-faced doors
- Available as 1800 x 800mm, 1800 x 1200mm, 2100 x 800mm and 2100 x 1200mm sheets

45mm insulated door panel – FD30 Fire Rated

- 45mm high density cork-filled door panels are ideal for raised and fielded panels
- FD30 Fire Rating
- Available as 1800 x 900mm and 1800 x 1200mm sheets

Both Products available from

- Stock in Redwood, European Oak, Sapele and Iroko with other species and sizes available to order
- External MDF-clad panels ideal for painting, are available in sheets of 2440 x 1220mm



Everything wood should be

West England
t: 01865 860350
f: 0800 085 9860

East England
t: 01865 860351
f: 0800 085 3748

Scotland
t: 0141 440 0060
f: 0141 445 5736

Ireland
t: +44 (0) 1865 860620
f: +44 (0) 1865 860305

e: marketing@timbmet.com
www.timbmet.com